

NVIDIA RTX[™] SERVER FOR SCALABLE VISUALIZATION SOLUTIONS ON TYAN THUNDER HX FA77-B7119 SERVER DESIGN GUIDE

VERSION: 1.0

TABLE OF CONTENTS

Chapt	er 1.	SOLUTION OVERVIEW	1
Chapter 2.		SOLUTION DETAILS	2
2.1	Solutio	n Configuration	3

Chapter 1. SOLUTION OVERVIEW

NVIDIA RTX Server[™] is a validated combination of qualified partner systems hosting NVIDIA Quadro RTX 6000 or RTX 8000 GPUs and Quadro Sync II cards providing the most advanced display technologies and interfaces to create the ultimate visual workspace for maximum productivity and dynamic large-scale visualization. Easily deploy and manage single or multiple displays on a desktop, drive head-mounted displays, build expansive digital signage walls, and create immersive high-resolution stereoscopic environments.

NVIDIA RTX[™] Server for SVS sets a new standard for professional synchronized display deployments, requiring unparalleled rendering and synchronized graphics performance, all with breakthrough possibilities that realtime ray tracing and AI can provide.

Chapter 2. SOLUTION DETAILS

NVIDIA RTX Server for SVS is a reference design comprised of (a) NVIDIA Quadro RTX 8000 or RTX 6000 graphics cards; (b) Quadro Sync II cards and (c) Tyan Thunder HX FA77-B7119. This validated solution provides unprecedented graphics scaling with 8 GPUs driving up to 32 displays with no modifications required to the applications or scaling down the resolution.

NVIDIA Quadro RTX 8000 and RTX 6000, powered by the NVIDIA Turing[™] architecture and the NVIDIA RTX platform, brings the most significant advancement in computer graphics in over a decade to professional workflows. New RT Cores and Tensor Cores bring the power of realtime ray tracing and AI-enhanced workflows to millions of design and creative professionals. Combined with NVIDIA NVLink[™] technology, RTX 8000 scales graphics memory and performance to drive the most demanding rendering, AI, and visual computing workloads.

NVIDIA Quadro Sync II solutions enable the creation of dazzling ultra-high resolution, perfectly synchronized displays to meet the visualization and presentation needs across industries. Designed for flexibility and scalability, Quadro Sync boards connect to select NVIDIA Quadro GPUs, synchronizing them with the displays or projectors attached to them. Quadro Sync also enables NVIDIA Quadro Mosaic[™] technology on those synchronized displays and projectors, providing an easy way to scale the resolution of any application across multiple GPUs.

Products from TYAN feature design enhancements specifically developed for enterprise computer room and data center environments. These highly stable, space-efficient products are very attractive to OEMs and System Integrators designing next generation rackmount server solutions for a wide array of applications.

2.1 SOLUTION CONFIGURATION

Table 1 outlines the system configuration utilized to complete the rigorous NVIDIA NVQual verification as well as the NVIDIA RTX Server validation process.

Table 1: Solution compor	nents
--------------------------	-------

Component	Vendor & Model	Details
System	Tyan Thunder HX FA77B7119	 Dual-Socket Intel 2nd Gen Xeon[®] Scalable Processors (24) DIMM slots supporting up to 3TB DDR4-2667
Graphics	8x Quadro RTX 6000 / 8x Quadro RTX 8000 4x Quadro RTX NVLink HB bridge 2-slot 2x Quadro Sync II card	 GPU memory: 24GB / 48GB CUDA cores: 4,608 Tensor cores: 576 RT cores: 72

Notice

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Information furnished is believed to be accurate and reliable. However, NVIDIA Corporation assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. No license is granted by implication of otherwise under any patent rights of NVIDIA Corporation. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all other information previously supplied. NVIDIA Corporation products are not authorized as critical components in life support devices or systems without express written approval of NVIDIA Corporation.

Trademarks

NVIDIA, the NVIDIA logo, and DGX are trademarks or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

© 2019 NVIDIA Corporation. All rights reserved.